

SHOWA

**381**



Embossed microporous nitrile coating over engineered microfibre

**[ FEATURES**

- Embossed microporous nitrile palm finish
- SHOWA engineered microfibre yarns (0.52 denier)
- High abrasion resistance level 4
- Ultra-light weight: 19 g
- Palm Thickness : 0.90mm
- Excellent fitting due to optimal liner design

**[ BENEFITS**

- Abrasion resistance lasts twice as longer as SHOWA 380 (8000 cycles vs 4000)
- Embossed nitrile palm finish disperses oil away to increase grip and longevity in light oily environments
- The 0.84mm finger thickness provides an excellent level of tactility and sensitivity
- Microfibre properties boost vapour permeation and enhances breathability thus drier hands and less sweat
- Exceptional suppleness, ultra-comfort and hand fitting thanks to the combination of microfibre and spandex
- A flexible glove designed for easy movement and extended wear
- No latex allergy risks

**[ INDUSTRY**



**Aerospace**



**Airports & Ports**



**Automotive**



**Construction**



**DIY**



**Engineering**



**Mechanical**



**Mining**



**Packaging**



**Warehousing & Distribution**

**[ IDEAL APPLICATIONS**

- Intricate parts handling
- Light assembly of oil-coated pieces
- Mechanical engineering
- Automotive repairs & maintenance
- Mechanical and engineering
- Shuttering
- Dry & oily parts assembly
- Component Assembly
- General Purpose
- Heavy Equipment Operation
- Supervising
- Tool Operation
- Transporting



**MATERIAL**

- Engineered yarn
- Microfibre
- Seamless knit

**COATING**

- Microporous nitrile



**NORMS**



SHOWA

**381**



**PACKAGING**

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



**SIZES**

- S
- M
- L
- XL
- XXL



**COLOUR**

- Grey w/ black palm



**[ YOU MIGHT ALSO BE INTERESTED IN**

SHOWA  
**382**



**MATERIAL**

Fibres techniques

**COATING**

Nitrile microporeux

**CATEGORY**

General Purpose

SHOWA  
**380**



**MATERIAL**

Nylon

**COATING**

Microporous nitrile

**CATEGORY**

General Purpose

SHOWA  
**376R**



**MATERIAL**

Nylon

**COATING**

Foam nitrile

**CATEGORY**

General Purpose

SHOWA  
**S-TEX 581**



**MATERIAL**

Kevlar

**COATING**

Microporous nitrile

**CATEGORY**

Cut

**[ USER INSTRUCTIONS**

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

**[ DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

SHOWA International | WTC - Tower I - Strawinskyaan 1817 - 1077 XX Amsterdam - The Netherlands

[showagroup.eu](http://showagroup.eu) | [info@showagroup.eu](mailto:info@showagroup.eu)

© SHOWA Group 2018 | All rights reserved