

SHOWA

382

SHOWA 382 microporous nitrile coated and silicone-free glove prevents fingerprint to metal sheet and glass.

[FEATURES

- SHOWA engineered microfiber yarns (0,52 denier)
- Embossed microporous nitrile palm finish
- Silicone-free and latex-free
- OEKO-TEX approved
- High abrasion resistance level 4
- Ultra-light weight: 19 g, Palm Thickness : 0,90mm
- Excellent fitting due to optimal liner design
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand

[BENEFITS

- Embossed nitrile palm finish disperses oil away to increase grip and longevity in light oily environments.
- Silicone-free means no transfer of silicone contaminations to metal parts prior to painting and production control for reduction of silicone contamination.
- No finger print on glass and metal parts
- The 0.84mm finger thickness provides an excellent level of tactility and sensitivity.
- Microfibre properties boost vapour permeation and enhances breathability thus drier hands and less sweat.
- Exceptional suppleness, ultra-comfort and hand fitting thanks to microfibre.
- No latex allergy risk by removing latex rubber band for the cuff edge

[INDUSTRY



Aerospace



Airports & Ports



Automotive



Glass



Mechanical



Packaging



Warehousing & Distribution

[IDEAL APPLICATIONS

- Intricate parts handling
- Light assembly of oil-coated pieces
- Metal stamping
- Mechanical engineering
- Automotive repairs & maintenance
- Dry & oily parts assembly
- Component Assembly



MATERIAL

- Engineered yarn
- Microfibre
- Nylon

COATING

- Microporous nitrile



NORMS



SHOWA

382



PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



SIZES

- S
- M
- L
- XL
- XXL



COLOUR

- Navy blue



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
380



MATERIAL

Nylon

COATING

Mikroporöses
Nitril

CATEGORY

General
Purpose

SHOWA
381



MATERIAL

Technische
Garne

COATING

Mikroporöses
Nitril

CATEGORY

General
Purpose

[USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved