





Latex palm coating over acrylic/cotton/polyester liner

FEATURES

- EN 407:2004 Contact heat Level 2; contact temperature up to 250 °C (482 °F) for 15 seconds
- Coated palm
- Elasticated cuff
- Rough finish over entire surface
- Anatomical shape
- Seamless knit

BENEFITS

- A comfortable, flexible glove that is resistant to abrasion and very pleasant to wear in cold weather
- Protects the hand in damp environments or against aggressive detergents or alcohols
- Breathable back of hand to reduce perspiration
- Surface provides tactile feel and better grip
- Greater hygiene
- Designed for easy movement and continuous wear
- No irritation by seams in contact with the skin
- Low-soil colour

IDEAL APPLICATIONS

• Heavy equipment handling



Agriculture



Airports & Ports



Gardening



Municipal Services



Warehousing & Distribution



MATERIAL

- Acrylic
- Cotton
- Polyester Seamless knit

COATING





NORMS













YOU MIGHT ALSO BE INTERESTED IN



USER INSTRUCTIONS

Do not use where there are chemical, electrical, high-temperature or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. This glove is designed for an intense activity down to 0°C. Designed to protect at temperature down to -30°C, for short or intermittent contact.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands showagroup.eu | info@showagroup.eu © SHOWA Group 2018 | All rights reserved