

SHOWA  
**495**



Full PVC coating, extra coating over entire hand on cotton/ removable acrylic liner

[ **FEATURES**

- Fully coated, extra coating over entire hand
- Topstitched edge
- Rough finish over entire surface
- Special hydrocarbon treatment
- Anatomical shape
- Seamless knit
- Removable acrylic lining

[ **BENEFITS**

- A flexible, soft glove that absorbs perspiration, for ultra comfortable extended wear and with good mechanical resistance.
- Seals and protects the hand against chemicals while remaining flexible, up to -20°C
- Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- Surface provides tactile feel and better grip
- Greater hygiene
- Effective cold protection, with easy clean lining
- Designed for easy movement and continuous wear
- Extended protection on the forearm

[ **INDUSTRY**



**Agriculture**



**Airports & Ports**



**Chemical**



**Commercial Fishing**



**Mechanical**



**Oil and Gas**



**Utilities**

[ **IDEAL APPLICATIONS**

- Chemical spraying & treatment



**MATERIAL**


- Cotton
- Removable insulated acrylic
- Seamless knit

**COATING**

- PVC



**NORMS**



SHOWA  
**495**



**PACKAGING**

- 10 Pair per polybag
- 6 Polybags per case
- 60 Pair per case



**SIZES**

- M
- L
- XL



**COLOUR**

- Blue



**THICKNESS**

- 1.50mm



**[ YOU MIGHT ALSO BE INTERESTED IN**

SHOWA  
**460**



**MATERIAL**  
Cotton  
**COATING**  
PVC  
**CATEGORY**  
Cold

SHOWA  
**465**



**MATERIAL**  
Cotton  
**COATING**  
PVC  
**CATEGORY**  
Cold

SHOWA  
**490**



**MATERIAL**  
Cotton  
**COATING**  
PVC  
**CATEGORY**  
Cold

**[ USER INSTRUCTIONS**

Do not use where there are chemical, electrical, high-temperature or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. This glove is designed for an intense activity down to 0°C. Designed to protect at temperature down to -30°C, for short or intermittent contact.

**[ DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands  
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved