



SHOWA

Unsupported, full nitrile coating with textured finish

FEATURES

- Unsupported, unlined
- 100% nitrile
- 0.56mm thick
- Bisque grip
- 480mm length
- Chlorinated



BENEFITS

- Provides chemical resistance against a broad range of solvents, oils, animal fats and other chemicals
- Mechanical resistance
- Bisque finish grip makes wet work easier and safer
- Ergonomic design maximizes comfort

INDUSTRY



Agriculture



Automotive



Chemical



Gardening



Municipal Services

IDEAL APPLICATIONS

- Chemical spraying & treatment
- Handling light chemicals in agriculture, horticulture
- Light assembly of oil-coated pieces
- Painting & spray workshops
- Coating preparation
- Washing & cleaning



Unsupported

COATING

Nitrile



NORMS





EN 3<u>88:201</u>6











SHOWA

747



PACKAGING

- 12 Pair per polybag
- 6 Polybags per case
- 72 Pair per case



SIZES

- L
- XLXXL



COLOUR

Light green





YOU MIGHT ALSO BE INTERESTED IN

727



MATERIAL
Unsupported
COATING
Nitrile
CATEGORY
Chemical

730



MATERIAL
Cotton flock
COATING
Nitrile
CATEGORY
Chemical

SHOWA **737**



MATERIAL
Unsupported
COATING
Nitrile
CATEGORY
Chemical

731



MATERIAL
Unsupported
COATING
Biodegradable
CATEGORY
Chemical

USER INSTRUCTIONS

Do not use where there are electrical, thermal or entanglement risks. Discard used gloves in compliance with local regulations. Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance. Store in a dry place, away from the light.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.