

SHOWA

878



Unlined, unsupported butyl coating

[FEATURES

- Unlined butyl rubber
- 0.70mm thick
- 350mm long
- Rolled cuff
- Smooth grip

[BENEFITS

- Protection against ketones, alcohols, nerve agents
- Provides the highest permeation resistance to gases and water vapors of any protective material used to make gloves
- Superior resistance to highly corrosive acids

[INDUSTRY



Chemical



Municipal Services

[IDEAL APPLICATIONS

- Chemical spraying & treatment
- Coating preparation
- Police & defense



MATERIAL

- Unsupported

COATING

- Butyl



NORMS



SHOWA

878



PACKAGING

- 12 Pair per polybag
- 1 Polybags per case
- 12 Pair per case



SIZES

- M
- L
- XL
- XXL



COLOUR

- Black



THICKNESS

- 0.70mm



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
874



MATERIAL
Unsupported
COATING
Butyl
CATEGORY
Chemical

SHOWA
874R



MATERIAL
Unsupported
COATING
Butyl
CATEGORY
Chemical

[USER INSTRUCTIONS

Do not use where there are electrical, thermal or entanglement risks. Discard used gloves in compliance with local regulations. Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved