

SHOWA



A0150

Uncoated antistatic nylon/acrylic liner

[FEATURES

- Uncoated
- Elasticated cuff
- Standard finish
- Without special treatment
- Surface resistivity 10⁶ to 10⁷
- Seamless knit

[BENEFITS

- A light, elastic low-lint glove, resistant to deformation and with antistatic properties
- Optimal dexterity and tactile feel retained
- Minimal allergy risks
- No irritation by seams in contact with the skin
- Great freedom of movement for the wrist

[INDUSTRY



Aerospace



Automotive



Cleanrooms



Electronics



Printing

[IDEAL APPLICATIONS

- Intricate parts handling
- Mechanical and engineering
- Semiconductors
- Cleanroom
- Integrated circuits
- Microelectronic



MATERIAL

- Acrylic
- Nylon
- Seamless knit

COATING

- Uncoated



NORMS



SHOWA

A0150



PACKAGING

- 10 Pair per polybag
- 24 Polybags per case
- 240 Pair per case



SIZES

- S
- M
- L
- XL



COLOUR

- Grey & white



USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved