

SHOWA

DURACoil 346

Latex coating over engineered DURACoil liner reinforced with HPPE

FEATURES

- Multifilament polyester wrapping DURACoil liner reinforced with HPPE
- EN 388:2016 Cut Level C
- ANSI/ISEA 105-16: A3
- Waterproof latex coated palm
- 13-gauge liner
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand
- Seamless knit
- Breathable open back design

BENEFITS

- Increased cut resistance performance due to engineered DURACoil wrapping technology
- Improved grip coating for enhanced performance
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- High level of flexibility and dexterity due to advanced grip technology
- Seamless knit designed to prevent irritation
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- A flexible, light glove providing effective protection against cuts
- Cost-efficient gloves that can be laundered and re-used
- Multi purpose cut glove at a nominal price

INDUSTRY



Construction



DIY



Glass



Manufacturing



Municipal Services



Warehousing & Distribution

IDEAL APPLICATIONS

- Decoration
- Guttering & drain piping
- Insulation
- Screw & nail setting
- Glass & window handling
- Component Assembly
- Washing & cleaning
- Quality control



MATERIAL

- Engineered yarn
- HPPE
- Polyester

COATING

- Latex



NORMS



SHOWA

DURACoil 346



PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



SIZES

- S
- M
- L
- XL



COLOUR

- Grey



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA DURACoil 546



MATERIAL
HPPE
COATING
Polyurethane
CATEGORY
Cut

SHOWA 341



MATERIAL
Nylon
COATING
Latex
CATEGORY
General Purpose

SHOWA 341



MATERIAL
Nylon
COATING
Latex
CATEGORY
General Purpose

SHOWA 306



MATERIAL
Nylon
COATING
Latex
CATEGORY
General Purpose

[USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved