

SHOWA

# DURACoil 386

Microporous nitrile coating over engineered DURACoil liner reinforced with HPPE

## FEATURES

- Multifilament polyester wrapping DURACoil liner reinforced with HPPE
- EN 388:2016 Cut Level C
- ANSI/ISEA 105-16: A3
- Microporous nitrile coated palm for good grip & aeration
- Excellent fitting due to optimal liner design
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand
- Seamless knit
- High abrasion resistance level 4

## BENEFITS

- Increased cut resistance performance due to engineered DURACoil wrapping technology
- Microporous nitrile coating protects the hand from oils and abrasions while remaining breathable
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- High level of flexibility and dexterity due to advanced grip technology
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- Embossed nitrile palm finish disperses oil away to increase grip and longevity in light oily environments
- Cost-efficient gloves that can be laundered and re-used

## INDUSTRY



Aerospace



Airports & Ports



Automotive



Construction



Engineering



Manufacturing



Mechanical



Packaging

## IDEAL APPLICATIONS

- Intricate parts handling
- Light assembly of oil-coated pieces
- Mechanical and engineering
- Automotive repairs & maintenance
- Dry & oily parts assembly
- Component Assembly
- Mechanical engineering



## MATERIAL

- Engineered yarn
- HPPE
- Polyester

## COATING

- Microporous nitrile



## NORMS



SHOWA

# DURACoil 386



## PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



## SIZES

- S
- M
- L
- XL
- XXL



## COLOUR

- Grey



## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
**DURACoil 546**



**MATERIAL**  
HPPE

**COATING**  
Polyurethane

**CATEGORY**  
Cut

SHOWA  
**381**



**MATERIAL**  
Engineered yarn

**COATING**  
Microporous nitrile

**CATEGORY**  
General Purpose

SHOWA  
**380**



**MATERIAL**  
Nylon

**COATING**  
Microporous nitrile

**CATEGORY**  
General Purpose

## [ USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

### Get in touch

SHOWA International | WTC - Tower I - Strawinsky laan 1817 - 1077 XX Amsterdam - The Netherlands  
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved