

SHOWA

DURACoil 546W

White reinforced polyurethane coating over engineered DURACoil liner reinforced with HPPE

FEATURES

- Multifilament polyester wrapping DURACoil liner reinforced with HPPE
- EN 388:2016 Cut Level C
- ANSI/ISEA 105-16: A3
- Polyurethane coated palm for good grip & aeration
- Lightweight, flexible liner with elastic knitted wrist
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand
- Seamless knit
- High abrasion resistance level 4
- Reinforced PU coating for increased abrasion resistance

BENEFITS

- Increased cut resistance performance due to engineered DURACoil wrapping technology
- PU foamed coating protects the hand from oils and abrasions while remaining breathable
- Improved grip coating for enhanced performance
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- High level of flexibility and dexterity due to advanced grip technology
- Seamless knit designed to prevent irritation
- Light colour helps identify soiling and contamination
- Ultra-comfortable multi-purpose glove with durable cut resistant properties for precision handling
- Cost-efficient gloves that can be laundered and re-used
- Multi purpose cut glove at a nominal price

INDUSTRY



Aerospace



Automotive



Laboratory



Manufacturing



Mechanical



Metallurgy



Pharmaceutical

IDEAL APPLICATIONS

- Intricate parts handling
- Laboratory, pharma & analyses
- Canning
- Cleanrooms
- Component Assembly
- White goods
- Mechanical engineering



MATERIAL

- Engineered yarn
- HPPE
- Polyester

COATING

- Polyurethane



NORMS



Cat. II
0120



EN 388:2016
4X42C



SHOWA

DURACoil 546W



PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



SIZES

- S
- M
- L
- XL
- XXL



COLOUR

- White



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
DURACoil 546



MATERIAL
HPPE

COATING
Polyurethane

CATEGORY
Cut

SHOWA
542



MATERIAL
HPPE

COATING
Polyurethane

CATEGORY
Cut

[USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskyalaan 1817 - 1077 XX Amsterdam - The Netherlands

showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved