

SHOWA

DURACoil 576

Foamed nitrile over $\frac{3}{4}$ dipped nitrile coating, over engineered DURACoil liner reinforced with HPPE

FEATURES

- Multifilament polyester wrapping DURACoil liner reinforced with HPPE
- EN 388:2016 Cut Level C
- ANSI/ISEA 105-16: A3
- Nitrile, $\frac{3}{4}$ coated, with an extra foamed nitrile finish on palm
- 13-gauge liner
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand
- Seamless knit
- High abrasion resistance level 4

BENEFITS

- Increased cut resistance performance due to engineered DURACoil wrapping technology
- Foamed nitrile coating protects the hand from oils and abrasions while remaining breathable
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- High level of flexibility and dexterity due to advanced grip technology
- Liquid-proof to end of coated area
- Optimal grip performance in wet & oily conditions
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- Cost-efficient gloves that can be laundered and re-used

INDUSTRY



Aerospace



Automotive



Construction



Engineering



Glass



Manufacturing



Mechanical



Oil and Gas

IDEAL APPLICATIONS

- Light assembly of oil-coated pieces
- Glass & window handling
- Mechanical and engineering
- Dry & oily parts assembly
- Heavy equipment handling
- Canning
- Mounting & dismantling



MATERIAL

- Engineered yarn
- HPPE
- Polyester

COATING

- Foam nitrile
- Nitrile



NORMS



SHOWA

DURACoil 576



PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



SIZES

- S
- M
- L
- XL
- XXL



COLOUR

- Grey/black



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
376R



MATERIAL

Nylon

COATING

Foam nitrile

CATEGORY

General Purpose

SHOWA
S-TEX 376



MATERIAL

Polyester

COATING

Foam nitrile

CATEGORY

Cut

SHOWA
DURACoil 577



MATERIAL

Engineered yarn

COATING

Foam nitrile

CATEGORY

Cut

[USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved