

SHOWA

# DURACoil 577

Foamed nitrile over fully dipped nitrile coating, over engineered fiber reinforced with HPPE

## FEATURES

- Multifilament polyester wrapping DURACoil liner reinforced with HPPE
- EN 388:2016 Cut Level C
- ANSI/ISEA 105-16: A3
- Fully coated nitrile, with an extra nitrile finish on palm for good grip & aeration
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand
- Seamless knit
- High abrasion resistance level 4

## BENEFITS

- Increased cut resistance performance due to engineered DURACoil wrapping technology
- Foamed nitrile coating with a film nitrile coating providing high abrasion resistance while remaining breathable
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- High level of flexibility and dexterity due to advanced grip technology
- Liquid-proof to end of coated area
- Optimal grip performance in wet & oily conditions
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- Cost-efficient gloves that can be laundered and re-used

## INDUSTRY



Aerospace



Automotive



Construction



Engineering



Glass



Manufacturing



Mechanical



Oil and Gas

## IDEAL APPLICATIONS

- Glass & window fixing
- Mechanical and engineering
- Plumbing
- Dry & oily parts assembly
- Canning
- Mounting & dismantling
- Heavy equipment handling



## MATERIAL

- Engineered yarn
- HPPE
- Polyester

## COATING

- Foam nitrile
- Nitrile



## NORMS



SHOWA

# DURACoil 577



## PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



## SIZES

- S
- M
- L
- XL
- XXL



## COLOUR

- Grey/black



## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
**377**



### MATERIAL

Nylon

### COATING

Foam nitrile

### CATEGORY

General Purpose

SHOWA  
**S-TEX 377**



### MATERIAL

Polyester

### COATING

Foam nitrile

### CATEGORY

Cut

## [ USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## Get in touch

SHOWA International | WTC - Tower I - Strawinskylaan 1817 - 1077 XX Amsterdam - The Netherlands

[showagroup.eu](http://showagroup.eu) | [info@showagroup.eu](mailto:info@showagroup.eu)

© SHOWA Group 2018 | All rights reserved