

SHOWA

# S-TEX 581

Microporous foamed nitrile palm coating over Hagane Coil® liner (Stainless Steel/Nylon/Polyester) reinforced with Kevlar®

## FEATURES

- 13 gauge engineered Hagane Coil® liner with Kevlar®
- EN 407:2004 Contact heat Level 2; contact temperature up to 250 °C (482 °F) for 15 seconds
- EN 388 cut level E
- Embossed microporous nitrile palm finish
- Ergonomic design hand mold that replicates the natural curves
- Seamless knit

## BENEFITS

- Lightweight glove with high cut protection performance
- Excellent cut resistance performance due to engineered fibre
- Embossed nitrile palm finish disperses oil to increase grip and longevity in light oily environments
- Foam nitrile coating provides an abrasion resistance level of 4 and extended usage
- Microporous nitrile coating grants exceptional grip while allowing warm air and moisture from inside to escape, thus keeping your hands dry
- Breathable back of hand to reduce perspiration
- Designed for easy movement and continuous wear
- Seamless knit designed to prevent irritation

## INDUSTRY



Automotive



Construction



Glass



Mechanical



Metallurgy



Utilities



Warehousing & Distribution

## IDEAL APPLICATIONS

- Automotive repairs & maintenance
- Light assembly of oil-coated pieces
- Mechanical and engineering
- Glass & window fixing
- Glass & window handling
- Install electrical wiring
- Trunking installation
- Internal fixing
- Screw & nail setting
- Steel erecting
- Steel fixing
- Bottling
- Dry & oily parts assembly



## MATERIAL

- Kevlar
- Nylon
- Polyester
- Seamless knit

## COATING

- Microporous nitrile



## NORMS



SHOWA

# S-TEX 581



## PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



## SIZES

- S
- M
- L
- XL
- XXL



## COLOUR

- Grey/black



## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
**4561**



**MATERIAL**  
Kevlar  
**COATING**  
Sponge nitrile  
**CATEGORY**  
Cut

SHOWA  
**S-TEX KV3**



**MATERIAL**  
Aramid knit  
**COATING**  
Latex  
**CATEGORY**  
Cut

## [ USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## Get in touch

SHOWA International | WTC - Tower I - Strawinskyalaan 1817 - 1077 XX Amsterdam - The Netherlands  
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved