

# **CT135**

Excellent performance against chemical permeation & durability in handling chemical with confident

# DESCRIPTION

Nitrile flock-lined unsupported glove

## FEATURES

- Unsupported 100% nitrile
- Flock-lined
- Sand pebble texture finishing
- Solvent & chemical resistance gloves
- Premium grade Acrylonitrile Butadiene rubber
- Specially formulated for improved dexterity & durability
- Minimal finger fatigue
- Food safe

#### COATING

Nitrile

#### BENEFITS

- Provides chemical resistance against a broad range of solvents, oils, animal fats and other chemicals
- > For long lasting mechanical resistance
- > Textured finishing grip makes wet work easier and safer
- Ergonomic design maximizes comfort

## APPLICATIONS

- Chemical spraying, treatment & blending
- Laboratory testing
- Handling chemicals in agriculture
- > Heavy assembly of oil-coated pieces
- Painting & spray workshops
- Coating preparation
- Washing & cleaning

## INDUSTRY

- Machinery
- Agriculture
- Automotive
- Chemical
- Municipal services
- Printing
- Food processing
- Cleaning industry
- Oil & gas

# Buts constraints Total and Total and total

# PACKAGING

- > 12 Pairs per polybag
- > 12 Polybags per carton
- 144 Pairs per carton

#### LENGTH

330mm +/- 30mm

# THICKNESS

0.40mm +/- 0.10mm (Palm area)

#### SIZES

- ➤ 7/S
- ≻ 8/M
- > 9/L
- ≻ 10/XL

# COLOUR

Green

## STANDARDS





#### USER INSTRUCTIONS:

Protection against mechanical risks. Discard used gloves in compliance with local regulations. Clean the glove with a damp cloth to remove contamination. Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance and the differentiation between mixtures and pure chemicals. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

Excia Resources Sdn Bhd (1193050-P) F-3-6, Pacific Place, Jalan PJU 1A/4A, Ara Damansara, 47301 Petaling Jaya, Selangor D.E., Malaysia. Tel: +603-7629 2321 | Fax: +603-7629 2231 Email: marketing@excia.com.my | Website: www.excia.asia



All product specifications, statements, information and data in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the information contained in this datasheet is applicable to the respective product stated.

Version 1.6

\*Image for illustration purpose only