


TT515 Cut Resistance


Lightweight with superior cut performance to reduce risk of injury

HPPE



Stainless Steel Wire

Spandex + Nylon



Nitrile Foam Grip Technology

Nitrile Foam

Thin Film Nitrile

Liner



BENEFITS

- Lightweight for superior grip performance and greater comfortability.
- Cut level D protection to prevent cut injury.
- Superior fitting for long working hours.
- Outstanding dexterity for fine work.
- Anti-static feature that minimizes electrostatic discharge from damaging the product.
- High abrasion resistance enhances durability and wear time.

FEATURES

- Lightweight
- Comfort fit with mid-level cut resistance
- Easy to handle precise job
- Anti-static
- Silicone free
- Touch screen



PRODUCT SPECIFICATION

Packaging

- 10 Pairs per polybag
- 12 Polybags per carton
- 120 Pairs per carton

Length

220mm - 280mm

Thickness

0.92mm

Colour

Grey

Sizes

- 7/S
- 8/M
- 9/L
- 10/XL

Coating

Nitrile

Material

15-Gauge HPPE stainless steel + Spandex + Nylon

APPLICATIONS



Machinery



Automotive



Semiconductor



Transportation



Aerospace



Construction



Glass Manufacturing

STANDARDS



EN 388:2016



4X42D

EN 1149-1

