

TT515

Lightweight with superior cut performance to reduce risk of injury

DESCRIPTION

Nitrile palm coated glove

FEATURES

- Lightweight
- Comfort fit with mid-level cut resistance
- Easy to handle precise job
- Anti-static
- Silicone free
- Touch screen

MATERIAL

15-Gauge HPPE Stainless steel + Spandex + Nylon

COATING

Nitrile

BENEFITS

- Lightweight for superior grip performance and greater comfortability
- Cut level D protection to prevent cut injury
- Superior fitting for long working hours
- Outstanding dexterity for fine works
- Anti-static feature that minimizes electrostatic discharge from damaging the product
- High abrasion resistance enhances durability and wear time

APPLICATIONS

- Hardware assembly works
- Machining parts and precision handling
- Electronic components handling
- Cabling and wiring works
- Glass and metal stamping
- General maintenance

INDUSTRY

- Machinery
- Automotive
- Semiconductor
- Transportation
- Aerospace
- Construction
- Glass manufacturing



PACKAGING

- 10 Pairs per polybag
- 12 Polybags per carton
- 120 Pairs per carton

LENGTH

220mm - 280mm

THICKNESS

0.92mm

SIZES

- 7/S
- 8/M
- 9/L
- 10/XL

COLOUR

Grey

STANDARDS

EN 388:2016



4X42D

EN 1149-1

USER INSTRUCTIONS:

Gloves provide protection from mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The levels of performance mentioned are only valid for the palm of the glove. The protection against risks or hazards which are not mentioned in this document is not warranted.

**Image for illustration purpose only*