

DATA SHEET

CE119

Excellent chemical resistance performance with good grip and extended length

DESCRIPTION

Neoprene flock-lined unsupported glove

FEATURES

- Flock-lined ≻
- ⊳ Premium grade neoprene rubber
- ۶ **Diamond texture finishing**
- ⊳ Straight cuff
- ⊳ Smooth outer finishing
- ⊳ AQL: 1.5
- ⊳ Extended length

COATING

Neoprene

BENEFITS

- Excellent chemical resistance to animal fats, oil, and solvents ≻ allows handling chemical works with confident
- ≻ Diamond texture finishing provide good grip in dry, wet and oily conditions
- \triangleright Bacteriostatic properties preserve cleanliness and hygiene

APPLICATIONS

- Heavy assembly of oil-coated pieces ≻
- ۶ Chemical spraying, treatment & blending
- ⊳ Chemical handling & mixing
- ⊳ Painting & spray workshops
- ⊳ **Coating preparation**
- \triangleright Maintenance work

INDUSTRY

- Machinery ≻
- ≻ Oil & gas
- ⊳ Chemical
- Automotive ≻
- ≻ **Municipal services**



PACKAGING

- ≻ 6 Pairs per polybag
- \triangleright 10 Polybags per carton
- \triangleright 60 Pairs per carton

LENGTH

380mm ± 10mm

THICKNESS

0.78mm ± 0.07mm

SIZES

- 7/S \succ
- \triangleright 8/M
- \triangleright 9/L \triangleright 10/XL

COLOUR

Black

STANDARDS









USER INSTRUCTIONS:

*Image for illustration purpose only

Protection against mechanical risks. Discard used gloves in compliance with local regulations. Clean the glove with a damp cloth to remove contamination. Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance and the differentiation between mixtures and pure chemicals. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

Excia Resources Sdn Bhd (1193050-P) F-3-6, Pacific Place, Jalan PJU 1A/4A, Ara Damansara, 47301 Petaling Jaya, Selangor D.E., Malaysia. Tel: +603-7629 2321 | Fax: +603-7629 2231 Email: marketing@excia.com.my | Website: www.excia.asia



All product specifications, statements, information and data in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the information contained in this datasheet is applicable to the respective product stated.

Version 1.4