

# **GT337**

Double palm coating provide superior grip performance in dry, wet and oily conditions

### DESCRIPTION

Nitrile fully coated glove

#### **FEATURES**

- Foam nitrile palm double coated ≻
- **High abrasion resistance** ≻

#### MATERIAL

13 Gauge polyester

#### COATING

Nitrile

#### BENEFITS

- Double palm coating provides superior grip in dry, wet ≻ and oily conditions
- Second palm coated layer acts against liquid ≻ penetration
- ⊳ Foam nitrile coating increased flexibility
- ≻ High abrasion resistance enhances durability and wear time
- Good dexterity for fine work ⊳
- Superior fitting for long working hours ⊳

#### **APPLICATIONS**

- Heavy-duty tasks ≻
- ≻ Machine handling
- Working and molding sheet metal ≻

#### INDUSTRY

- ≻ Machinery
- ⊳ Automotive
- ≻ Construction
- ⊳ Transportation
- ⊳ Warehousing and distribution



#### PACKAGING

- $\triangleright$ 12 Pairs per polybag
- ≻ 10 Polybags per carton
- $\triangleright$ 120 Pairs per carton

## LENGTH

240mm

THICKNESS

7/S  $\geq$ 

$\triangleright$	8/M
-	0/11

 $\triangleright$ 9/L

- 10/XL
- 11/XXL

COLOUR

Blue

#### **STANDARDS**



USER INSTRUCTIONS:

Gloves provide protection from mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The levels of performance mentioned are only valid for the palm of the glove. The protection against risks or hazards which are not mentioned in this document is not warranted.

Excia Resources Sdn Bhd (1193050-P) F-3-6, Pacific Place, Jalan PJU 1A/4A, Ara Damansara, 47301 Petaling Jaya, Selangor D.E., Malaysia. Tel: +603-7629 2321 | Fax: +603-7629 2231 Email: marketing@excia.com.my | Website: www.excia.asia



All product specifications, statements, information and data in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the information contained in this datasheet is applicable to the respective product stated.

Version 1.1

\*Image for illustration purpose only