

TT520

Highest cut resistance with reinforced crotch & extra length for wrist protection

DESCRIPTION

Nitrile palm coated glove

FEATURES

- Cut level F performance
- High abrasion resistance
- Reinforced crotch
- Extra length

MATERIAL

13-Gauge HPPE + Stainless steel

COATING

Nitrile

BENEFITS

- Highest cut protection with cut level F performance to prevent cut injury
- Excellent abrasion resistance enhances durability and wear time
- Reinforced crotch for extra cut protection
- Extra length for wrist protection

APPLICATIONS

- Hardware assembly works
- Machining parts and precision handling
- Electronic components handling
- Cabling and wiring works
- Glass and metal stamping
- General maintenance

INDUSTRY

- Machinery
- Automotive
- Agriculture
- Horticulture
- Transportation
- Aerospace
- Construction
- Glass industry
- Mining
- Logistics



PACKAGING

- 10 Pairs per polybag
- 6 Polybags per carton
- 60 Pairs per carton

LENGTH

350mm

THICKNESS

-

SIZES

- 7/S
- 8/M
- 9/L
- 10/XL

COLOUR

Light Grey

COUNTRY OF ORIGIN

China

STANDARDS



USER INSTRUCTIONS:

Gloves provide protection from mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The levels of performance mentioned are only valid for the palm of the glove. The protection against risks or hazards which are not mentioned in this document is not warranted.

**Image for illustration purpose only*