

TT555

Excellent grip in light wet/oil condition with nitrile micro granular coating

DESCRIPTION

Nitrile micro granular palm coated glove

FEATURES

- Micro granular surface finishing
- High abrasion resistance

MATERIAL

13 Gauge HPPE + Glass fiber

COATING

Nitrile micro granular

BENEFITS

- Excellent grip performance in light wet/oil condition
- Superior cut protection with cut level D performance to prevent cut injury
- High abrasion resistance enhances durability and wear time
- Good dexterity for fine work
- Superior fitting for long working hours

APPLICATIONS

- Hardware assembly works
- Machining parts and precision handling
- Glass and metal stamping
- General maintenance

INDUSTRY

- Machinery
- Automotive
- Agriculture
- Horticulture
- Transportation
- Aerospace
- Construction
- Glass industry
- Logistics



PACKAGING

- 10 Pairs per polybag
- 12 Polybags per carton
- 120 Pairs per carton

LENGTH

240mm

THICKNESS

-

SIZES

- 7/S
- 8/M
- 9/L
- 10/XL
- 11/XXL

COLOUR

Grey

STANDARDS



USER INSTRUCTIONS:

Gloves provide protection from mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The levels of performance mentioned are only valid for the palm of the glove. The protection against risks or hazards which are not mentioned in this document is not warranted.

**Image for illustration purpose only*