

# TN747

Superior cut resistance offers double protection when used as inner glove to prevent cut injury

## DESCRIPTION

HPPE non coated glove

## FEATURES

- Cut level F performance
- Can be used as inner glove
- Lightweight and soft
- Form fitting design

## MATERIAL

18-Gauge HPPE + Special Steel + Nylon + Spandex

## COATING

-

## BENEFITS

- Superior cut protection with highest cut level F performance to prevent cut injury
- Can be used as inner glove for double protection from cut injury
- Outstanding dexterity for fine work
- Superior fitting for long working hours

## APPLICATIONS

- Hardware assembly works
- Machining parts and precision handling
- Cabling and wiring works
- Glass and metal stamping
- General maintenance

## INDUSTRY

- Automotive
- Construction
- Glass industry
- Machinery
- Marine
- Manufacturing
- Food processing



## PACKAGING

- 10 Pairs per polybag
- 12 Polybags per carton
- 120 Pairs per carton

## LENGTH

230mm ±10mm

## THICKNESS

-

## SIZES

- 7/S
- 8/M
- 9/L
- 10/XL
- 11/XXL

## COLOUR

Dark Grey

## STANDARDS



## USER INSTRUCTIONS:

Gloves provide protection from mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The levels of performance mentioned are only valid for the palm of the glove. The protection against risks or hazards which are not mentioned in this document is not warranted.

*\*Image for illustration purpose only*

